2003 SONY MOBILE

PRODUCT GUIDE



CDX-CA710X FM/AM Compact Disc Player

- CD/MD Control w/Custom File™ memory
- XT-XM1 Control
- DSO, EQ7
- 52W x 4 High Power
- XM Ready, CD Text
- SSIR-EXA Tuner
- Flip-down Detachable Face
- 18FM + 12AM memory presets
 Station Memo™, Disc Memo™, Memo List functions
 3-color, 13-segment LED Display
- Supplied Wireless Card Remote (RM-X118)
- Optional Wired Rotary Remote (RM-X4S)
- Indicates step-up

Audio Power Specifications

POWER OUTPUT AND TOTAL HARMONIC DISTORTION

23.2 watts per channel minimum continuous average power into 4 ohms, 4 channels driven from 20 Hz to 20 kHz with no more than 5% total harmonic distortion.

CD Player Section

Signal-to-noise ratio 90 dB

Frequency response 10 - 20,000 Hz Wow and flutter Below measurable limit

Tuner Section

FM

87.5 - 107.9 MHz Tuning range External antenna connector Antenna terminal Intermediate frequency 10.7 MHz/450 kHz Usable sensitivity 9 dBf

Selectivity 75 dB at 400 kHz

Signal-to-noise ratio 67 dB (stereo), 69 dB (mono) Harmonic distortion at 1 kHz 0.5% (stereo), 0.3% (mono)

35 dB at 1 kHz Separation 30 - 15,000 Hz Frequency response

AM

Tuning range 530 – 1,710 kHz External antenna connector Antenna terminal Intermediate frequency 10.7 MHz/450 kHz Sensitivity 30 μV

15

Power Amplifier Section

Outputs Speaker outputs (sure seal connectors)

Speaker impedance 4 - 8 ohms

 $52 \text{ W} \times 4 \text{ (at 4 ohms)}$ Maximum power output

General

Input

Outputs Audio outputs (rear)

> Power antenna relay control terminal Power amplifier control terminal Telephone ATT control terminal BUS control input terminal

BUS audio input terminal Remote controller input terminal Antenna input terminal

Tone controls Bass ± 10 dB at 62 Hz Treble ± 10 dB at 16 kHz

Loudness +8 dB at 100 Hz +2 dB at 10 kHz

Power requirements 12 V DC car battery (negative ground) Dimensions Approx. $178 \times 50 \times 177 \text{ mm}$

 $(7\ 1/8 \times 2 \times 7\ in.)\ (w/h/d)$ Approx. $182 \times 53 \times 161 \text{ mm}$

Mounting dimensions (7 1/4 \times 2 1/8 \times 6 3/8 in.) (w/h/d)

Mass Approx. 1.2 kg (2 lb. 10 oz.)

Supplied accessories Parts for installation and connections (1 set)

Front panel case (1)

Card remote commander RM-X118

Harness Plug Configuration

Battery

• Rear Preamp Output • 8fs. 1-Bit D/A Converter

Active Servo Control

• 60 Degree Install

• CD-R/RW Playback



Plug shown with wires facing viewer.

Pin Number	Wire Color	Description
1	White	Left front +
2	Green	Left rear +
3	Purple	Right rear +
4	Gray	Right front +
5	Blue/white	AMP Remote
6	Blue	ANT Remote
7	Red	Accessory
8	Black	Ground
9	White/black	Left front -
10	Green/black	Left rear -
11	Purple/black	Right rear -
12	Gray/black	Right front -
13	Sky blue	ATT
14		

Note

This unit cannot be connected to a UniLink digital preamplifier or equalizer.

Design and Specifications subject to change without notice.



Yellow

2003 SONY MOBILE PRODUCT GUIDE

CDX-CA710X FM/AM Compact Disc Player



